

549,435

Rec'd PCT/PTO 22 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/057039 A1

(51) International Patent Classification⁷: C22B 1/10, 5/14,
B01J 8/18, 8/44, F27B 15/02, 15/10

6100 (AU). NUBER, Dirk [DE/DE]; Haingrabenstrasse 26, 60488 Frankfurt am Main (DE). STRÖDER, Michael [DE/DE]; Dürerstrasse 77, 61267 Neu-Anspach (DE).

(21) International Application Number:

PCT/EP2003/013500

(74) Agent: KEIL & SCHAAFHAUSEN; Cronstettenstrasse 66, 60322 Frankfurt am Main (DE).

(22) International Filing Date: 1 December 2003 (01.12.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(26) Publication Language: English

Published:

— with international search report

[Continued on next page]

(54) Title: METHOD AND PLANT FOR THE HEAT TREATMENT OF SOLIDS CONTAINING IRON OXIDE USING A FLUIDIZED BED REACTOR



WO 2004/057039 A1

(57) Abstract: The present invention relates to a method and a plant for the heat treatment of solids containing iron oxide, in which fine-grained solids are heated to a temperature of 700 to 1150°C in a fluidized bed reactor (8). To improve the utilization of energy, it is proposed to introduce a first gas or gas mixture from below through at least one gas supply tube (9) into a mixing chamber region (15) of the reactor (8), the gas supply tube (9) being at least partly surrounded by a stationary annular fluidized bed (12) which is fluidized by supplying fluidizing gas. The gas velocities of the first gas or gas mixture and of the fluidizing gas for the annular fluidized bed (12) are adjusted such that the Particle-Froude-Numbers in the gas supply tube (9) are between 1 and 100, in the annular fluidized bed (12) between 0.02 and 2, and in the mixing chamber (15) between 0.3 and 30.



- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.